



DALCON SIZE LIST – METRIC

DESCRIPTION	PAGE
TABLE OF CONTENTS	1
P.T.F.E. Film-Sheet - Standard	2
P.T.F.E. Film-Sheet - Superior	3
P.T.F.E. Sheets	4
P.T.F.E. Cut Flat Sheets	5



PRODUCT: PTFE FILM/SHEET - STANDARD
GRADE: dalconTM 001 NATURAL

Thickness mm	Tolerance mm	Metre/Roll (Approx.)	1000mm Wide	1200mm Wide	1500mm Wide
		1200/1500mm Wide	Kgs per linear metre		
0.50	+0.08 - 0.00	255	1.1772*	1.4126*	1.7657
0.60	+0.08 - 0.00	205	1.3952	1.6742	2.0927
0.70	+0.08 - 0.00	182	1.6132	1.9358	2.4197
0.80	+0.08 - 0.00	160	1.8312	2.1974	2.7467
1.00	+0.08 - 0.00	130	2.2672*	2.7206*	3.4006
1.25	+0.12 - 0.00	97	2.8558	3.4270	4.2837
1.50	+0.15 - 0.00	80	3.4335	4.1202	5.1503
2.00	+0.20 - 0.00	65	4.5780	5.4936	6.8670
2.50	+0.20 - 0.00	55	5.6680	6.8016	8.5020
3.00	+0.25 - 0.00	39	6.8125	8.1750	10.2187
3.50	+0.25 - 0.00	35	7.7390	9.2868	11.6085
4.00	+0.30 - 0.00	31	9.0470	10.8564	13.5705
4.75	+0.30 - 0.00	30	10.682	12.818	-

WEIGHTS STATED ARE APPROXIMATE AND FOR GUIDE PURPOSES ONLY

Product Specification

Natural Conforms to BS EN ISO 13000 FbP2.
 Also available BS EN ISO 23000 FbP1, subject to quotation.

Quality Certification

Commercial Certificate of Conformity.
 Material Analysis Report.
 BS EN ISO 9001: 2000 Certificate.


Information

* Indicates item normally held in stock.
 Colours & other Filled Grades available subject to quotation. Graphite, Bronze, MOS₂,
 Conductive, Glass, Stainless Steel, Carbon/Coke.
 Sizes not Stock Items, will be subject to minimum of whole roll.
 Suitable to finish to the nominal sizes stated.

Dalau UK

Dalau Limited,
 Ford Road,
 Clacton on Sea,
 Essex CO15 3DZ
Tel: +44 (0) 1255 220220
Fax: +44 (0) 1255 221122

Email: sales@dalau.com
www.dalau.com



PRODUCT: PTFE FILM/SHEET - SUPERIOR
GRADE: dalconTM 001 NATURAL

>0< mm	Tolerance mm	Metre/Roll (Approx.)	1000mm Wide	1200mm Wide	1500mm Wide
		1200/1500mm Wide	Kgs per linear metre		
0.025	+/- 0.00125	5000	0.057	0.068	-
0.05	+0.01 - 0.00	2331	0.1199	0.1439	0.180
0.07	+0.02 - 0.00	1500	0.1744	0.209	0.262
0.10	+0.03 - 0.00	1200	0.2507	0.3008	0.3759
0.12	+0.03 - 0.00	940	0.3052	0.3532	0.4415
0.15	+0.03 - 0.00	795	0.3597	0.4316	0.5394
0.20	+0.03 - 0.00	605	0.4687	0.5624	0.7029
0.25	+0.03 - 0.00	505	0.5777	0.6901	0.8625
0.30	+0.03 - 0.00	410	0.6867	0.8240	1.0299
0.40	+0.03 - 0.00	315	0.9047	1.0856	1.3569
0.50	+0.08 - 0.00	255	1.1772	1.4126	1.7657



WEIGHTS STATED ARE APPROXIMATE AND FOR GUIDE PURPOSES ONLY

Product Specification
 Natural Conforms to BS EN ISO 13000 FaP2 <=0.07mm Thick
 BS EN ISO 13000 FbP2 >=0.10mm Thick.

Also available BS EN ISO 13000 FaP1 <=0.07mm Thick
 BS EN ISO 13000 FbP1 >=0.10mm Thick, subject to quotation.

Quality Certification
 Commercial Certificate of Conformity.
 Material Analysis Report.
 BS EN ISO 9001: 2000 Certificate.

Information
 Orders will be subject to minimum of whole roll.
 Suitable to finish to the nominal sizes stated.



PRODUCT: PTFE SHEETS
GRADE: dalconTM 001 NATURAL

Thickness mm	Thickness Tolerance (mm)	600mm x 600mm Weight Kgs/Each	1000mm x 1000mm Weight Kgs/Each	1200mm x 1200mm Weight Kgs/Each
1.00	+0.08 -0.00	0.60	2.27 *	3.26 *
1.50	+0.15 -0.00	1.23	3.43	4.80 *
2.00	+0.20 -0.00	1.63	4.58	6.58 *
2.50	+0.20 -0.00	2.00	6.00	8.00
3.00	+0.25 -0.00	2.40	6.81	9.81 *
3.50	+0.25 -0.00	-	7.74	12.30
4.00	+0.30 -0.00	3.26	11.00	13.03
5.00	+15% -0.00	4.50	13.00	18.00
6.00	+15% -0.00	5.40	16.00	21.00
8.00	+15% -0.00	7.20	20.00	28.50
10.00	+15% -0.00	9.00	25.50	35.50
12.00	+15% -0.00	10.80	31.00	43.00
15.00	+15% -0.00	13.50	39.50	53.00
20.00	+20% -0.00	18.00	51.00	72.00
25.00	+20% -0.00	23.00	62.00	90.00
30.00	+20% -0.00	26.00	74.00	106.00
40.00	+20% -0.00	35.00	90.00	141.00
50.00	+20% -0.00	44.00	120.00	184.00

WEIGHTS STATED ARE APPROXIMATE AND FOR GUIDE PURPOSES ONLY

Product Specification

Conforms to BS EN ISO 13000 FbP2 <=4mm Thick
 BS EN ISO 13000 SbS2 >=5mm Thick.
 Also available BS EN ISO 13000 FbP1 <=4mm Thick
 BS EN ISO 13000 SbS1 >=5mm Thick, subject to quotation.

Quality Certification

Commercial Certificate of Conformity.
 Material Analysis Report.
 BS EN ISO 9001: 2000 Certificate.



Information

* Indicates item normally held in stock.
 Sheet Size Tolerance: +30 mm -0.00.
 Colours & other Filled Grades available subject to quotation. Graphite, Bronze, MOS₂,
 Conductive, Glass, Stainless Steel, Carbon/Coke.
 Suitable to finish to the nominal sizes stated.

Dalau UK

Dalau Limited,
 Ford Road,
 Clacton on Sea,
 Essex CO15 3DZ
 Tel: +44 (0) 1255 220220
 Fax: +44 (0) 1255 221122

Email: sales@dalau.com
 www.dalau.com



PRODUCT: PTFE CUT FLAT SHEETS			
GRADE: dalconTM 001 NATURAL			
Thickness mm	Thickness Tolerance (mm)	1000mm x 1000mm Weight Kgs/Each	1200mm x 1200mm Weight Kgs/Each
1.00	+0.08 -0.00	2.27*	3.26 *
1.50	+0.15 -0.00	3.43*	4.80 *
2.00	+0.20 -0.00	4.58*	6.58 *
2.50	+0.20 -0.00	6.00	8.00
3.00	+0.25 -0.00	6.81*	9.81 *
3.50	+0.25 -0.00	7.74	11.15 *
4.00	+0.30 -0.00	9.05	13.03 *

WEIGHTS STATED ARE APPROXIMATE AND FOR GUIDE PURPOSES ONLY

Product Specification
 Conforms to BS EN ISO 13000 FbS2.
 Also available BS EN ISO 13000 FbS1, subject to quotation.

Quality Certification
 Commercial Certificate of Conformity.
 Material Analysis Report.
 BS EN ISO 9001: 2000 Certificate.

Information
 * Indicates item normally held in stock.
 Sheet Size Tolerance: +30 mm -0.00.
 Colours & other Filled Grades available subject to quotation. Graphite, Bronze, MOS₂,
 Conductive, Glass, Stainless Steel, Carbon/Coke.
 Suitable to finish to the nominal sizes stated.